



Advantages

This cable is new generation of USB3.0 hybrid cable. Its build-in unique SuperTT technology is capable of realizing mutual conversion between USB3.0 AND USB2.0 protocols, so as to enable USB2.0 equipment to share the super speed bandwidth(5Gbps) of USB3.0. It is highly recommended to use with all series WINSAFE USB3.0 HD PTZ camera for long distance application

Features

- ※ Support USB3.0/USB2.0/1.1 devices
- ※ The maximum cable length can be up to 50m
- ※ The maximum transition speed can be up to 5Gbps
- ※ A substantial increase in USB2.0 device bandwidth with Build-in SuperTT technology
- ※ Without additional power supply
- ※ With locking screw holes
- ※ Hot-plugging
- ※ No driver& Anti-jamming

Technical Specification

Model No.	USB3-20
Cable Length	20M
Interface	
Hot side	USB3.0 Standard-A Plug(with locking screws), USB2.0 Micro-B Receptacle, Auxiiary powerSupply for device >2W power dissipation
Device Side	USB3.0 Standard-A Receptacle(with lockingthreads)
Data Rate	USB3.0 Super Speed, Up to 5Gbps, backward compatible with USB2.0/1.1
Power Dissipation	0.94W
Physical/Environmental	
Dimension of the end	Hot side: 44mm/27mm/13mm, Device side:82mm/26mm/14.5mm
Weight of the end	TBD
Cable Diameter	3mm
Operating Temperature	0 - 55°C
Storage Temperature	-20 - 80°C

※※※Product specification are subject to change without notice ※※※