



Product Overview

- * ONVIF2.4
- * Support P2P function
- * Optional function: Alarm, Audio, SD Card slot
- * 8pcs Array 42Mil LED, IR range up to 150M
- * 7" full metal body construction, IP66 rate protection
- * Compatible with HIKVISION、DAHUA、XM、Video park NVR .etc
- * Compatible with CMS、UC2、Milestone、NUUO and AXXON platform.etc
- * Intelligent IR illumination & power consumption is variable, dependant the zoom factor

Technical Specification

Model No.	WS-BTHD812	
DSP	HI3516C	HI3516D
Sensor	IMX323(2.0MP)	AR0521(5.0MP)
HD Signal Format	HD:1080p/30fps, 1080p/25fps	2592*1944@15fps 2592*1944@22fps
Lens	f=4.7mm-94mm	f=4.7mm-94mm
Power	DC12/3A	
Working Temperature	(-40℃~+60℃)	
Consumption	≤15W	
Voice intercom	Support	
Tilt Rotation Range	0-93°	
Pan Rotation Range	0-360°	
Horizontal Rotation Speed	0-45°/s	
Pan Rotation Speed	0-30°/s	
Auto Flip	Support Horizontal 180°, Vertical 93°	
IR Distance	240M	
Led	4 PCS Laser led+11 PCS IR led	
Inspection teams	3 groups(Max.16 points, dwell time user electable)	
IR control	PWM	
AB Scan position	User programmabel(scan speed 1-9 levels setting available)	
Mechanical zero calibration	Support	
Preset	220	
Digital zoom	20X	
Compression	H.264/H.265M-JPEG	
Audio	G711, PCM	
Audio frequency	1 audio (Optional)	

P2P	Android, Iphone
Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
APP	Hisee
Software Control	IE, CMS, Management Platform
Compatibility	HIKVISION ,DAHUA, XM NVR , Milestone and AXXON platform
Network Safe	HTTPS, 802.1X, IP ADDRESS FILTERING
Quick command	PELCO instruction set
Connector	RJ45
Quick instruction	PELCO
IP Code	IP66
Thunder Proof	Transient voltage 6000V
Size	W310mm*D310mm*H440mm
Weight	N.W 2.95KG/G.W 4.5KG

***** Product specification are subject to change without notice *****

www.winsafecctv.com