




NDI



## Features


- ※ 1/2.8" EXMOR CMOS image sensor, up to 2.14MP
- ※ Support NDI | HX output
- ※ 20X optical zoom, 12x digital zoom, up to 59.5°FOV
- ※ H.265 video compression, dual stream
- ※ Come with IR remote controller
- ※ Control Interface: RS-232IN/IR, RS-232 OUT/RS485
- ※ Image flip function for stand and suspended installations
- ※ Standard VISCA & Pelco communication protocols

## Dimensional Drawing




- |            |                    |
|------------|--------------------|
| 1 USB      | 6 Audio            |
| 2 TF card  | 7 RS-232IN/IR      |
| 3 Ethernet | 8 RS-232OUT/RS-485 |
| 4 DVI-D    | 9 DC12V            |
| 5 HD-SDI   |                    |

## Accessories



Wall Bracket



Ceiling Plate

## Technical Specification

<b>Model No.</b>	<b>AMC-NE220NV3</b>
<b>Camera</b>	
Image Sensor	1/2.8" Exmor CMOS, 2.14MP
Video Standard(HD)	1080p60,1080p50,1080p30,1080p25,1080i60,1080i50,720p60,720p50
Focal	f = 4.7mm - 94mm
IRIS	F1.6 - F3.5
Zoom	Optical: 20X, Digital: 12X
Field of View	59.5° - 2.9°
Focus	Auto, Manual, PTZ Trigger AF, One push
Min.Illumination	0.5Lux(Color), 0.1Lux(B/W)
Shutter Speed	1/1 - 1/10,000s
AGC	Auto/Manual
White Balance	Auto, Indoor, Outdoor, One push, Manual, Auto Track
AE Control	Auto, Manual, Shutter Priority, Iris Priority, Intelligence
S/N Ratio	Above 50dB
<b>PTZ</b>	
Pan Range	-170° - +170°
Tilt Range	-30° - +90°
Pan Speed	0.1° - +120°/s
Tilt Speed	0.1° - +80°/s
Preset Number	256
OSD	Yes
Image Flip	Yes
<b>Network</b>	
Max,Image Size	1920x1080
Frame Rate	HD:50Hz:50fps(1920x1080) 60Hz:60fps(1920x1080)
Video Compression	H.265,H.264
Audio Compression	AAC
Protocol	HTTP,RTSP,RTMP,RTP,TCP,UDP,ONVIF
Dual Stream	Support
Simultaneous Users	up to 10 users
<b>Interface</b>	
HD Video Output Interface	HDMI, 3G-SDI
Audio	One Line In; One Line out
Ethernet	RJ45(NDI   HX),100M
Local Storage	TF card, up to 64GB
USB	USB2.0
Control Interface	RS-232IN/IR, RS-232OUT/RS-485
<b>General</b>	
Control Protocol	VISCA and Support Daisy Chain, PELCO-D, PELCO-P
Address	0 - 63
Power Supply	DC12V
Working Temp	0°C - +40°C
Storage Temp	-20°C - +60°C
Dimension	243mm x 145mm x 163mm
Weight	1.2KG
Color	Grey
<b>***Product specification are subject to change without notice***</b>	